



BWS Waterproof Weighing Indicator

General Specifications

- Display 52mm digit LCD display, with white LED backlight
- Keyboard 7keys(Mechanical switch)
- Housing SST
- Max. Divisions 6,000e; 30,000d
- Load cell excitation voltage 5V/150mA
- ADC update $\leq 1/10$ second
- Operate Temp $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), rechargeable battery (6V/4Ah)
- Gross weight 3.2kg
- Packing Master carton 4 in 1 packing, dimension 0.093m^3 , 40 feet container can load 2200 machine, 20 feet container can load 1100 machine



- Easy to use-front panel configuration
- Application: 1. Zero 2. Accumulation 3. Check weighing 4. Net/gross shift 5. Weighing units conversion
- OIML approval from Delta(approval no.:DK0199.165)
- Keyboard lock function
- IP65 waterproof rate
- Selectable 1.2" LED display(BWS-E)
- Optional RS-232 interface, Blue tooth
- Optional analog output (0-10V/4-20mA)
- Optional setpoint output (HI/OK/LOW/BEEP)





BWS Waterproof Weighing Indicator

Model Number	Capacity	Readability	Division	Approx. weight	Approval
BWS	X	X	30,000d	2.0kg	CE
BWS-M	X	X	6,000e	2.0kg	CE, OIML
BWS-E	X	X	30,000d	3.2kg	CE

Options



Dimensions(mm)



Print formats



Head Office:
 The Filing Room (Ground Floor)
 Near Panari Hotel
 P.O Box 6863 -00200
 Tel: +020-2013976
 Mobile: 0722-303505
 0738-829064

Eldoret Office:
 KFA Building
 Opp Uchumi Supermarket
 Tel: 053 2032561
 Fax: 053 2063738
 Mobile: 0733-781832

info@scale-software.co.ke
 www.scale-software.co.ke